Republic of the Philippines
City of Cagayan de Oro
BIDS AND AWARDS COMMITTEE

cagayan de Oro
city of golden friendship

SUPPLEMENTAL/BID BULLETIN

ADDENDUM NO. 32 - 2025
17 September 2025

This Addendum No. 32 - 2025 is issued to modify or amend items in the Bidding Documents of the project, ***Supply and Delivery of Firetruck; PR No. 25-1998 dated May 02, 2025; SN 92a - 2025***. This shall form an integral part of the Bidding Documents.

Section VII. Technical Specifications of the Bidding Documents of the above-mentioned procurement, is hereby modified or amended as follows:

From	To
Firetruck Unit Specifications: High Power Direct-Injection OHC Intercooled Turbo Diesel Engine Transmission: Manual Transmission Displacement: 5,193cc Maximum Output: 110kW (150PS) / 2.600rpm (net) Maximum Torque: 404N.m (41.0kg-m) / 1,500-2,600rpm (net) Chassis: 8 Ton Differential: Original Heavy Duty 6 Wheeler 6 Stud Differential Truck Water Tank: Custom Made Corrugated Water Tank Water Capacity: 4000 Liters Water Capacity Tank Material: Constructed with non-corrosive Stainless Steel Tank Construction: Design: Side Corrugated Shape Design Water Movement Control; Provided with Baffles / Swash Partition Water Tank Lid: Original Imported Machine Pressed Molded European Grade Stainless Steel Round Water Tank Lid Assembly with Locking Turn Mechanism Drainages Designed with Drainage Outlet with Shut Off Valve Shock Absorbers: Equipped with 4 Sets European Grade Shock Absorber with Rubber Dampers to cushion the Tank and isolate it from any	**Firetruck** **Engine & Drivetrain** Engine Type: 6-cylinder, turbocharged, air-intercooled diesel Power Output: Increased from 110kW (150PS) to **162 HP @ 2500 rpm** Torque: Increased from 404 Nm to **850 Nm @ 1300 rpm** Displacement: Increased from 5,193 cc to **5,700 cc** Transmission: **8-speed manual**, multiple gear ratios Clutch: Hydraulic with air assist (non-asbestos) Differential: Heavy-duty 6-wheeler setup (retained) **Braking System** Main Brakes: Full-air brake system, dual-circuit Auxiliary Brake: Exhaust braking Parking Brake: Manual valve control with spring accumulators ABS: Included **Chassis & Suspension** Chassis Load Capacity: 8-ton GVW (Gross Vehicle Weight): 18,000 kg Suspension: Multi-leaf springs with shock absorbers (front & rear)

RISE CAGAYAN DE ORO

effect due to chassis whip and protected from undue stress or distortion when the vehicle is operating in uneven terrain or rough roads Water Level Indicator: Manual Type Water level indicator with Special Plastic Tubing with Aluminum Frame with Fittings		Axle Load Distribution: Improved front and rear load balance **Water/Foam System** Water Tank Capacity: 4,000 Liters Foam Tank Capacity: 1,000 Liters Fire Pump: Rear-mounted PL8/24 fire pump Monitor: West fire monitor turret Tank Design: Corrugated stainless steel tank with baffles (anti-sloshing) **Cabin & Controls** Cab Type: Semi-floating flat-top semi-cab Seats: ISRI high-back seats with full adjustment Instrument Panel: LCD instrument panel with speed, RPM, temperature, fuel, oil gauges Other Features: Electric windows, cruise control, pneumatic horns & wipers Navigation System: Beidou-compatible system **Lighting & Safety** Warning Lights: 16 warning lights, internal/external flashing lights Additional Lighting: Side and rear lights Safety Accessories: Aluminum alloy ladder, reflective tape **Firefighting Equipment** Included Equipment: Hoses, nozzles, boots, suits, crowbar, axe, bolt cutter, suction hoses, connectors Turret: Water monitor turret with accessories

For guidance and information of all concerned.

ATTY. JOEFFREY D. NAMALATA
BAC Chairperson